WIFI set-up

- Part 1-Connecting to your router
- 1. Connect the external WIFI device to the GTIL.
- 2. Power on the GTIL
- 2. Open your pc or cellphone
- 3. Your home network will detect the presence of a new Wireless connection

For example, in the picture below, you will see X2116640263692. This is a unique name. This is your wifi device name. It is also the serial number and also the Datalog pin. Write down this characters.



4. Connect to X2116640263692. It is the same in your cellphone when connecting to available wireless connection or WIFI.



5. You will then be prompted to enter security key. Enter 12345678 then press ok.



6. Check if you are connected.



7. Open internet browser. IE or Chrome or firefox is fine. Then in the address bar, type 192.168.8.66

Then press enter in your keyboard.



8. Enter username and password. Then press ok.

Username: admin

Password: admin

2 ht	tp://192.168.8.66 is requesting your username and password. T	he site says: "Wi-Fi Kit"
User Name:	admin	
Password:	•••••	
	OK Cancel	

9. This will be displayed. Select English.

C Photobucket O Diy Solar Ph	als 🖸 youtube	DivAudio 📴 botmai 👘 kai 🛤	C Q Search	
			nar no 🔘 hertzblastern's Bucket 🖤 toc solar 🛞 elab 🤐 dz. 🌒 ate-don 📁 n	
			中文 English	
※約信息	设备	PN	X2116440263692	
双直回号	软件	版本号		
尤社议直	WIF	王作模式	APSTA	
	WIF	版本号	V1.1	
	APM	DEC		
			X2116440263692	
			未当時的曲器	
		MACIECE	ACC523A08FA6	

10. This will be the interface setting between your home router and your GTIL WIFI. See the Network status in red "Connected router Failed".

N	X211644026369
/er	1.5.0.
MODE	APSTA
Ver	V1.1
IODE	
	X2116440263692
MAC	ACCF23A88FA7
MODE	
Network Status	Connected Router Failed

11. Click Wizard.

1 So	ft Ver	
t Ind		1.5.0.1
Set	FIMODE	APSTA
Kat W	IFI Ver	V1.1
AF	PMODE	
Set		X2116440263692
	MAC	ACCF23A88FA7
5		

12. You have to enter Network Name. Click Scan.

		中文 English
Router Seting Network Name(SSID) Note: case sensitive		Scanja
Encryption Method	WPA2PSK	1
Encryption Algorithm	AES	
Password		
	F Show Words	
	Enable 👤	
	0.0.0.0	
	0.0.0.0	
	0.0.0.0	

13. Click the name of your own wireless network. Press ok.

ST 40:A5:EF:10.77.4C 4 11 DMEDSL 00:13:33:DE:97.A4 61 11	161
DMEDSL 00:13:33:DE:97:A4 61 11	
and the second	

14. Press Ok again when you see this



15. Enter the password of your router. Press ok.

Note: ca	ise sensitive	PLDTHOME	=D'SL	Sca	n
Encrypt	ion Method	WPA2PSK			
Encrypt	tion Algorithm	AES	-		
Passwo	ard	Show W	ords		
	an IP address automatically	Enable	•		
		0.0.0.0			
		0.0.0.0			
		0.0.0.0			
		10.10.100.2	54		

16. Click next



17. enter new username and password if you wish. Remember them. . Then click next.

Current User Name	*300
New User Name	

18. click finish





19. Click system info



20. Change wireless connection. Connect to your router



21. Type again in your internet browser 192.168.8.66 and press enter on your keyboard.

See network status in green. Network success! If you are a newbie, if you reach this point, give yourself a pat on the back. Congratulations!

Info DEV PN	X2116440263692
Soft Ver	1.5.0.1
WIFI MODE	APSTA
WiFi Ver	V1.1
AP MODE	
SSID -	X2116440263692
IP :	192.168.8.66
MAC	ACCF23A8BFA7
STA MODE	
Network Status	Network Success
Router SSID	PLDTHOMEDSL
IP -	192.168.1.19
MAC	· ACCF23A8BFA6

PART2- REGISTERING YOUR DEVICE TO REMOTE SERVER

- 1. Open your internet browser.
- 2. Type www.shinemonitor.com
- 3. Click the drop down arrow in the upper right hand corner and select english



4. Click new user below the Login button.



5. Fill in the required information. Datalog PN is your wifi serial no. X211%\$#@%^^.

Phone no format example. 639171234567

http://www.shim/reg_en.html × 03 Mail-ra	ogel naval - Outlook 🗙 🕇			
(i) www.shinemonitor.com/reg_en.html			C Search	☆ 自 ♣ 佘 ♥ ☷
Most Visited 0 DIYPROJECTOR 🖾 Photobucket	🛈 Diy Solar Phils 💶 youtube 💮 DiyAudio 🧕 hotmai	l 🤞 bpi 🖪 solar fb 🔘 hertzbl	asterx's Bucket 🎯 tpc solar 🛞 elab 🌞 olx 🔞 abs-cbr	😏 TWITTER 🌞 Shinemonitor FERNAN ECD
and the second second	Register an account	Add a plant	Registration is complete	
	Register		Have an account? Log in	- Service
		me* 🛛 A hertzblaster		1 Sales
and the second sec	Passwo	rd* 🕞 ••••••		
	Password Confin	m* 🔂		
	Ema	il * • • 🖸 🗹		
		* 🧿 🔇		
		* N*		
		Next Step		
		The subscription of the su		

Then click next step.

6. I have no picture in the next step yet. But just fill in the required information. Plant name is any name you want. Then Press next

7. Then you should be able to complete registration and see your GTIL production. See red circle, should indicate normal. Feel free now to navigate and learn the information that will be helpful to you.

D O December 2 2222012 IX D HT-0002 X 2 menubierenharcommarX +			
			c 5
BG0 登录首家 想安全保存该网站的密码吗?(老型地带网络多公共地区不建议保存)			¢ ×
Shine Monitor & Soularmen *		Proprietor E	glish 👻
Plant Profiles Power Generation Overlear Device Management Alam Event Pla	ant Information Plant Analysis		
Image and the second	- Red Grap poor	0400 1300 1200	69
escritescontrol			

8. Using cellphone, in the home page (You must be logged out) www.shinemonitor.com

"Below the page, download the phone application IOS or android "smartclient for solar"



Use same username and password as your pc.

Sign up!



9. REMINDER- Always remember you username and password. WRITE IT DOWN OR SAVE ON YOUR PC.